

Replaces Greencare CoreMaster Parts Aerating Tines

Alloy Solid Tines



Alloy Solid Tines aerate without the work of cleaning up the mess of cores and debris left behind with conventional core aerating. R&R Solid Tines are manufactured from a special high-carbon steel bar and heat treated to RC45-48 in our own heat treat facility. They are available in all standard sizes but are especially popular in the smaller diameters for aerating in the summer months to relieve the stress on greens by allowing water, air and nutrients to easily flow into the root zone. With the combination of small holes and no cores, play can be resumed immediately.

Mounting Dia	Tine Length	Tip O.D.	Tip I.D.	Wall Thickness	R&R Part No.	Discounted Price Each
.375"	3.500"	.375"			R201420	
.730"	4.375"	.250"			R201425	
.730"	4.375"	.312"			R201426	
.730"	4.375"	.375"			R201427	
.730"	4.375"	.500"			R201428	

Standard Hollow Tines



Designed to remove a soil core, R&R Standard Hollow Tines are constructed from case hardened tubular steel and are the most economical tines available. Case hardening hardens the inner and outer surfaces of the tine wall to over RC55 for added wear.

Mounting Dia	Tine Length	Tip O.D.	Tip I.D.	Wall Thickness	R&R Part No.	Discounted Price Each
.730"	4.250"	.500"	.375"	.063"	R201348	
.730"	4.500"	.625"	.500"	.063"	R201290	

Alloy Machined Side-Eject Tines



Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

Mounting Dia	Tine Length	Tip O.D.	Tip I.D.	Wall Thickness	R&R Part No.	Discounted Price Each
.375"	3.500"	.330"	.200"	.062	R800650	
.375"	3.500"	.450"	.315"	.062"	R201630	
.375"	3.500"	.565"	.435"	.062"	R201631	
.375"	4.500"	.450"	.315"	.065"	R201632	
.375"	4.500"	.565"	.435"	.065"	R201633	
					R800651	

Alloy Shatter Tines



With their "+" shape, Shatter Tines relieve compaction and allow water, air and nutrients to flow in the root zones and beyond with virtually no visible surface disturbance. Because of their unique shape the aerating area is maximized while allowing play to be resumed immediately. R&R Shatter Tines are manufactured from special high-carbon alloy investment castings and heat treated to RC45-48 in our own facility to insure you of optimum quality.

Mounting Dia	Tine Length	Tip O.D.	Tip I.D.	Wall Thickness	R&R Part No.	Discounted Price Each
.730"	4.600"	.375"			R201548	
.730"	4.600"	.500"			R201565	



All original equipment manufacturers names and part numbers are used for identification purposes only, and we are in no way implying that our products are original equipment parts. Prices subject to change without notice.

R&R Products
 FEATURED PRODUCTS
 TURF EQUIPMENT
 POWER EQUIPMENT
 GOLF COURSE
 DRIVING RANGE
 ATHLETIC FIELD
 IRRIGATION
 WORK WEAR
 SAFETY & SECURITY
 TOOLS
 EQUIPMENT PARTS
 Equipment Parts
 EQUIPMENT PARTS
 404